

Supermicro MBD-X9SRL, Single SKT, Intel C602 Chipset, SATA, 2xGbE Bulk

Kod producenta: MBD-X9SRL-B



Form Factor	ATX
Dimensions	12" x 9.6"
CPU Socket	LGA 2011 (Socket R)
# of CPU sockets	1
Supported CPU's	Intel Xeon E5-2600v2 Intel Xeon E5-1600v2 Intel Xeon E5-2600 Intel Xeon E5-1600
Chipset	Intel C602 Patsburg
Memory Type	DDR3 ECC LRDIMM DDR3 ECC RDIMM DDR3 ECC UDIMM DDR3 non-ECC UDIMM
Memory Speed	1866 MHz 1600 MHz 1333 MHz 1066 MHz
# of DIMM's	8
Max Memory Size	512 GB
Integrated GPU	Matrox G200eW
# of PCIe x4 3.0	2
# of PCIe x8 3.0	4
# of PCIe x4 2.0	1
# of USB Ports	2 x USB 2.0 (rear) 6 x USB 2.0 (header) 1 x USB 2.0 Type A
# of SATA Ports	10
# of SATA DOM power	1
Storage Controllers	2 x AHCI iSATA 6Gb/s 4 x AHCI iSATA 3Gb/s 4 x sSATA 3Gb/s
Integrated RAID	0,1,5,10
# of Serial Ports	1 x Fast UART 16550 (rear) 1 x Fast UART 16550 (header)
# of 1GbE Ports	2 x RJ45
Network Controllers	Intel 82574L Dual Port Gigabit Ethernet
TPM	1 x TPM 1.2 20-pin Header
Uwagi	PCI-Express Slots Configuration: 2x PCI-E 3.0 x8 (in x16) slots 2x PCI-E 3.0 x8 slots 2x PCI-E 3.0 x4 (in x8) slots 1x PCI-E 2.0 x4 (in x8) slot

Product SKUs

MBD-X9SRL -B • X9SRL (Bulk Pack)

Physical Stats

Form Factor • ATX

Dimensions • 12" x 9.6", (30.5cm x 24.4cm)

Processor/Cache

CPU - Single Socket R (LGA 2011)
- Intel® Xeon® processor
E5-2600/1600
and **E5-2600/1600 v2** family[†]
(up to 12 cores and up to 130W)
† BIOS version 3.0 or above is required

Note † E5-1600 series CPU does not support LRDIMM type memory

System Memory

Memory Capacity - 8x 240-pin DDR3 DIMM slots
- Up to 512GB DDR3 ECC LRDIMM
- Up to 256GB DDR3 ECC RDIMM
- Up to 64GB DDR3 ECC/non-ECC UDIMM
Memory Type - 1866/1600/1333/1066MHz ECC
DDR3 SDRAM 72-bit, 240-pin gold-plated DIMMs
DIMM Sizes - 32GB, 16GB, 8GB, 4GB, 2GB, 1GB, 64GB LRDIMM
Memory Voltage - 1.5 V, 1.35 V
Error Detection - Corrects single-bit errors
- Detects double-bit errors (using ECC memory)

On-Board Devices

Chipset - Intel C602 chipset
SATA - SATA3 (6Gb/s) and SATA2 (3Gb/s)
- RAID 0, 1, 5, 10 support
- Intel® 82574L Dual Port Gigabit Ethernet
Network Controllers - Virtual Machine Device Queues
reduce I/O overhead
- Supports 10BASE-T, 100BASE-TX, and 1000BASE-T, RJ45 output
Video - Matrox G200eW 16MB DDR2 graphics

Input / Output

SATA - 2 SATA 3.0 ports (6Gb/s)
- 4 SATA 2.0 ports (3Gb/s)
SCU - 4 SATA ports (3Gb/s) via SCU
LAN - 2 RJ45 Gigabit Ethernet LAN ports
USB - 9 USB 2.0 ports total
(2 rear + 6 via header + 1 Type A)
Video - 1 VGA port
Keyboard/Mouse - 2 PS/2 Keyboard/Mouse ports
Serial Port / Header - 1 serial port, 1 by headers
DOM - 1 DOM (Disk on Module) power connector
TPM - 1 TPM Header

OS Compatibility

• Please reference the [OS Compatibility Chart](#) for details

Strona firmowa produktu:

<https://www.superstorage.pl/supermicro-mbd-x9srl-single-skt-intel-c602-chipset-sata-2xgbe-bulk-p-2639>.
Copyright ©2024 www.superstorage.pl | niedziela, 28 kwiecień 2024 Strona: 2 / 3

Chassis (Optimized for X9SRL)

2U Chassis - [CSE-823TQ-653LPB](#)
- To support motherboards based on Intel® Xeon® processor 5500/3500 series, **Revision K** or later chassis is recommended for most models. Please talk to your sales representative for details.

Expansion Slots

PCI-Express - 2 (x8) PCI-E 3.0 (in x16) slots
- 2 (x8) PCI-E 3.0 slots
- 2 (x4) PCI-E 3.0 (in x8) slots
- 1 (x4) PCI-E 2.0 (in x8) slot

System BIOS

BIOS Type - 64Mb SPI Flash EEPROM with AMI BIOS
- Plug and Play (PnP)
- APM 1.2
- DMI 2.3
- PCI 2.3
BIOS Features - ACPI 1.0 / 2.0 / 3.0 / 4.0
- USB Keyboard support
- Hardware BIOS Virus protection
- SMBIOS 2.7.1
- UEFI 2.3.1
- RTC (Real Time Clock) Wakeup

Management

Software - [SuperDoctor® III](#)
- Watch Dog
- NMI
- ACPI / APM Power Management
Power Configurations - Keyboard Wakeup from Soft-Off
- CPU Fan auto-off in sleep mode
- Power-on mode for AC power recovery

PC Health Monitoring

Voltage - Monitors for CPU Cores, +3.3V, +5V, ±12V, +5V Standby, VBAT, HT, Memory, Chipset Voltages.
- Total of 5 fan headers supporting up to 5 fans
- 5 fans with tachometer status monitoring
FAN - Status monitor for speed control
- Status monitor for on/off control
- Low noise fan speed control
- Pulse Width Modulated (PWM) fan connectors
- Monitoring for CPU and chassis environment
Temperature - CPU thermal trip support
- I°C temperature sensing logic
- Thermal Monitor 2 (TM2) support
- PECI
LED - CPU / System Overheat LED
- Suspend static indicator LED
- UID/Remote UID
Other Features - Chassis intrusion detection
- Chassis intrusion header
- Chipkill support
- RoHS, Halogen Free

