

Supermicro SuperChassis SC813MFTQ-R400CB 1U 4xLFF RED PSU

Kod producenta: CSE-813MFTQ-R400CB



Chassis Form Factor	Rack 1U
# of 3.5 hot-swap bays	4
Power Supply	Redundant
PSU Wattage	400W
PSU Certification	80+ Gold
Chassis Dimensions	437 x 43 x 503mm

Product SKUs

CSE-813MFTQ-R400CB • SuperChassis 813MFTQ-R400CB (Black)

Form Factor

1U chassis support for motherboard sizes - Micro ATX 9.6" x 9.6" or ATX 12" x 10"

Processor Support

Supports dual, single Intel® / AMD processors

Dimensions

- Height • 1.7" (43mm)
- Width • 17.2" (437mm)
- Depth • 19.85" (503mm)
- Gross Weight • 33.5 lbs (15.2kg)
- Available Colors • Black

Expansion Slots

1x Full-height AOC expansion slot

Drive Bays

- Hot-swap • 4x 3.5" Hot-swap SAS2 (6Gb/s) / SATA drive bays
- SAS or enterprise SATA HDD only recommended

SAS / SATA Backplane

1x SAS / SATA Backplane

Peripheral Drives

- Others • Front USB/COM tray in slim DVD bay (Optional)

Front Panel

- Buttons • Power On/Off button
- System Reset button
- Power LED
- LEDs • Hard drive activity LED
- 2x Network activity LEDs
- System Overheat LED

Motherboard (for CSE-813MFTQ-R400CB)

- | | |
|------------------------------|-----------------------------|
| X10DRL-C | X10DRL-CT |
| X10DRL-i | X10DRL-iT |
| X10SRH-CLN4F | X10SRi-F |
| X10SRL-F | X11SSH-CTF |
| X11SSH-F | X11SSH-LN4F |
| X11SSH-TF | X11SSi-LN4F |
| X11SSL | X11SSL-CF |
| X11SSL-F | X11SSL-nF |
| X11SSM | X11SSM-F |
| X9DRL-7F | X9DRL-EF |

Server(s) for SC813MFTQ-R400CB

- | | |
|----------------------------|---------------------------|
| 6017R-M7RF | 6018R-MTR |
| 5019S-MR | |

System Cooling

- | | |
|------|--|
| Fans | <ul style="list-style-type: none">• 4x 4cm 4-pin PWM fans• 2x additional fans optional; 6x fans total maximum |
|------|--|

Operating Environment (System)

- | | |
|---------------------------------------|--|
| Operating Temperature Range | <ul style="list-style-type: none">• 5°C ~ 35°C (41°F ~ 95°F) |
| Non-Operating Temperature Range | <ul style="list-style-type: none">• -40°C ~ 60°C (-40°F ~ 140°F) |
| Operating Relative Humidity Range | <ul style="list-style-type: none">• 8% ~ 90% (non-condensing) |
| Non-Operating Relative Humidity Range | <ul style="list-style-type: none">• 5% - 95% (non-condensing) |

Power Supply

- 400W Redundant Power Supplies w/Power Distributor, PMBus 1.2, I²C, and PFC
- | | |
|----------------------------------|--|
| AC Input | <ul style="list-style-type: none">• 100-240V, 50-60Hz, 6-3A |
| DC Output | <ul style="list-style-type: none">• +5V standby: 3A• +12V: 33A |
| DC Output With Power Distributor | <ul style="list-style-type: none">• +5V: 25A• +3.3V: 25A• -12V: 0.6A |

Regulatory (Power Supply)

- | | |
|---------------------------|--|
| Power Supply Safety / EMC | <ul style="list-style-type: none">• USA - UL listed, FCC• Canada - CUL listed• Europe/CE Mark• EN 60950/IEC 60950-Compliant |
|---------------------------|--|

Strona firmowa produktu:

<https://www.superstorage.pl/supermicro-superchassis-sc813mftq-r400cb-1u-4xlff-red-psu-p-2643.html>