

Supermicro SuperChassis SC813MT-410CB 1U 4xLFF FIX PSU

Kod producenta: CSE-813MT-410CB



Chassis Form Factor	Rack 1U
# of 3.5 hot-swap bays	4
Power Supply	Fixed
PSU Wattage	410 W
Chassis Dimensions	437 x 43 x 503mm



Product SKUs

CSE-813MT-410CB • SuperChassis 813MT-410CB
(Black)

Form Factor

1U chassis support for max. motherboard size - 12" x 10" ATX

Processor Support

Supports dual Intel® / AMD processors

Dimensions

Height • 1.7" (43mm)
Width • 17.2" (437mm)
Depth • 19.8" (503mm)
Gross Weight • 31 lbs (14.1kg)
Available Colors • Beige, Black

Expansion Slots

1x full-height, half-length PCI expansion slot (Riser Card Required)

Drive Bays

Hot-swap • 4x 3.5" Hot-swap SAS / SATA drive bays
• SAS or enterprise SATA HDD only recommended

SATA Backplane

1x SATA Backplane

Peripheral Drives

DVD-ROM • Slim DVD-ROM drive (Optional)

Front Panel

Buttons • Power On/Off button
• System Reset button
LEDs • Power LED
• Hard drive activity LED
• 2x Network activity LEDs
• System Overheat LED
Ports • 2x Front USB Ports
• 1x Serial COM Port

System Cooling

Fans • 4x 4cm 12,500 RPM PWM fans

Operating Environment (System)

Operating Temperature • 5°C ~ 35°C (41°F ~ 95°F)
Range
Non-Operating Temperature • -40°C ~ 60°C (-40°F ~ 140°F)
Range
Operating Relative Humidity • 8% ~ 90% (non-condensing)
Range
Non-Operating Relative Humidity • 5% - 95% (non-condensing)
Range

Power Supply

410W DC power supply (24-pin)

• Voltage Range = -36V to -72V
DC Voltage • Nominal Voltage = -48V
• Max Input Current = 18A @ -48V

DC Output • 5V + 3.3V ≤ 160W

+5V • 35.0 Amp

+5V standby • 3.0 Amp

+12V • 32.0 Amp

-12V • 0.5 Amp

+3.3V • 20.0 Amp

Regulatory (Power Supply)

Power Supply Safety / EMC • USA - UL listed, FCC
• Canada - CUL listed
• Europe/CE Mark
• EN 60950/IEC 60950-Compliant
• Germany - TUV Certified

Strona firmowa produktu:

<https://www.superstorage.pl/supermicro-superchassis-sc813mt-410cb-1u-4x1ff-fix-psu-p-2657.html>

