

Supermicro SuperChassis SC826BAC4-R920LPB 2U 12xLFF RED PSU

Kod producenta: CSE-826BAC4-R920LPB



Chassis Form Factor	Rack 2U
# of 3.5 hot-swap bays	12
Power Supply	Redundant
PSU Wattage	920W
PSU Certification	80+ Platinum

Product SKUs			
CSE-826BAC4-R920LPB • SuperChassis 826BAC4-R920LPB			Motherboard (for CSE- 826BAC4-R920LPB)
Form Factor			X10DRC-T4+ X10SRH-CLN4F X10DRH-iT X10DRH-C X10DRH-CLN4 X10DRC-LN4+ X10DRH-i X10DRH-CT X10DRH-iLN
• 2U chassis support max. motherboard size - ATX 12" x 10", E-ATX 12" x 13", EE-ATX 13" x 13.68". • Support up to ATX 12"x13" MB with rear 2.5" HDD option installed			
Processor Support			Systems Cooling
• Dual and Single Intel® and AMD processors			- 3 x 8cm high-performance PWM fan(s) - Optional 5 x 6cm 4pin high performance fan(s)
Dimensions			Fans
Height Width Depth Net Weight Gross Weight Packaging (W x H x L) Available Color - 3.5" (89 mm) - 17.2" (437 mm) - 25.5" (647 mm) - 40 lbs (18.14 kg) - 55 lbs (24.95 kg) - 26.7" (678 mm) x 11.4" (290 mm) x 34.5" (876 mm) - Black			
Expansion Slots			System Monitoring
- 7 low-profile expansion slot(s)			- Chassis intrusion switch
Drive Bays			Operating Environment (System)
- 12 x 3.5" hot-swap drive bay - Optional 2 x 2.5" hot-swap drive bay - 8x SAS3 12Gbps and 4x Hybrid (NVMe/SAS3) 3.5" HDD			Operating Temperature Range Non-Operating Temperature Range Operating Relative Humidity Range Non-Operating Relative Humidity Range - 5°C - 35°C (41°F - 95°F) - -40°C - 70°C (-40°F - 158°F) - 8% - 90% (non-condensing) - 5% - 95% (non-condensing)
Backplane			Power Supply
- 12-port 2U SAS3 12Gbps hybrid backplane, support up to 8x 3.5-inch SAS3/SATA3 HDD/SSD and 4x SAS3/SATA3/NVMe Storage Devices			1U 920W Redundant Platinum Super Quiet power supply W/PMbus Power Efficiency Total Output Power and Input AC Input Frequency Dimensions (L x W x H) Output Type +12V +5Vsb Power Distributor - 94% - 920W with Input 100 - 240Vac - 50-60Hz - 346 x 76 x 40 mm - Backplanes (gold finger) - Max: 75A / Min: 1A (100Vac - 240Vac) - Max: 4A / Min: 0A - PDB-PT826-8824 - O/P: 12V/135A - +5V Max: 40A - +3.3V Max: 24A - -12V Max: 0.6A
Front Panel			Certification
Buttons LEDs - Power On/Off button - System Reset Button - 2 Network Activity LEDs - Fan Fail/System Over Heat LED - HDD activity LED - Power Status LED - Unit Identification (UID) LED			Platinum Certified
			Regulatory (Power Supply)
			- BSMI - CCC - CE/EMC - FCC class B - TUV/CB - UL/CUL

Strona firmowa produktu:

<https://www.superstorage.pl/supermicro-superchassis-sc826bac4-r920lpb-2u-12xlff-red-psu-p-2668.html>