

Supermicro SuperChassis SC842i-500B 4U 5xLFF FIX PSU

Kod producenta: CSE-842i-500B



Chassis Form Factor	Rack 4U
# of 3.5 fixed bays	5
Power Supply	Fixed
PSU Wattage	500W
PSU Certification	80+ Bronze

Product SKUs	Motherboard (for CSE-842i-500B)	
CSE-842i-500B • SuperChassis 842i-500B (Black)		
Form Factor	H8SCM	H8SCM-F
Industrial Short-Depth 4U Rackmount supports E-ATX, ATX, Micro ATX motherboards; max. motherboard size 12" x 13"	H8SGL	H8SGL-F
	H8SML-7	H8SML-7F
	H8SML-i	H8SML-iF
	X10SL7-F	X10SLA-F
	X10SLH-F	X10SLL+-F
Processor Support	X10SLL-F	X10SLL-S
Supports dual, single Intel® / AMD processors	X10SLL-SF	X10SLM+-F
	X10SLM+-LN4F	X10SLM-F
Dimensions	X10SLX-F	X10SRH-CF
Height • 7.0" (178mm)	X10SRi-F	X10SRL-F
Width • 17.2" (437mm)	X11SSA-F	X9DRL-3F
Depth • 20.5" (521mm)	X9DRL-iF	X9SCI-LN4
• 26.4" (W) x 13.8" (H) x 31.5" (D)	X9SCL	X9SCL+-F
Packaging 670mm (W) x 350mm (H) x 800mm (D)	X9SCL-F	X9SCM
Gross Weight • 25 lbs (11.3kg)	X9SCM-F	X9SCM-iF
Available	X9SRE	X9SRE-3F
Colors • Black	X9SRE-F	X9SRH-7F
	X9SRH-7TF	X9SRi
	X9SRi-3F	X9SRi-F
	X9SRL-F	
Expansion Slots	System Cooling	
7x Tool-less Full-height, Full-length PCI Expansion Slots	Fans	• 1x Front Intake 9cm PWM cooling fan
Drive Bays	(Hot-plug)	• 2x Rear 8cm PWM cooling fans
Internal HDD Bays	System Monitoring	
• 5x 3.5" internal HDD Bays	Chassis intrusion switch	
• SAS or enterprise SATA HDD only recommended		
Peripheral Bay(s)	Operating Environment (System)	
• 3x 5.25" Peripheral Drive Bays	Operating Temperature	
• 1x Slim DVD-ROM (optional) Drive Bay	Range • 5°C ~ 35°C (41°F ~ 95°F)	
Front Panel	Non-Operating Temperature	
Buttons	Range • -40°C ~ 60°C (-40°F ~ 140°F)	
• Power On/Off button	Operating Relative Humidity	
• System Reset button	Range • 8% ~ 90% (non-condensing)	
• Power LED	Non-Operating Relative Humidity	
LEDs	Range • 5% - 95% (non-condensing)	
• Hard drive activity LED		
• 2x Network activity LEDs		
• System Overheat LED		
• Power Fail LED		
Ports		
• 2x USB 2.0 Ports		
	Power Supply	
	500W AC power supply w/ PFC	
	AC Voltage • 100 - 240V, 50-60Hz, 7-3.5 Amp	
	+5V • 20 Amp	
	+5V standby • 3 Amp	
	+12V1 • 17 Amp	
	+12V2 • 17 Amp	
	+12V3 • 17 Amp	
	+12V4 • 18 Amp	
	-12V • 0.5 Amp	
	+3.3V • 15 Amp	
		
	Certification	
	Bronze Certified	
	[Test Report]	
	Regulatory (Power Supply)	
	• USA - UL listed, FCC	
	• Canada - CUL listed	
	• Germany - TUV Certified	
	• Europe/CE Mark	
	• EN 60950/IEC 60950-Compliant	
	Power Supply Safety / EMC	

Strona firmowa produktu:
<https://www.superstorage.pl/supermicro-superchassis-sc842i-500b-4u-5xlf-fix-psu-p-2676.html>