

Supermicro SuperChassis SC743TQ-865B Tower/4U 8xLFF FIX PSU

Kod producenta: CSE-743TQ-865B



Chassis Form Factor	Tower/4U
# of 3.5 hot-swap bays	8
Power Supply	Fixed
PSU Wattage	865W
PSU Certification	80+

Product SKUs

CSE-743TQ-865B • SuperChassis 743TQ-865B (Black)

Form Factor

4U chassis support for max. motherboard size - 12" x 13" E-ATX

Processor Support

Supports dual, single Intel® / AMD processors

Dimensions

- Width • 7.0" (178mm)
- Height • 17.8" (452mm)
- Depth • 25.5" (648mm)
- Gross Weight • 56 lbs (25.4kg)
- Available Colors • Black

Expansion Slots

7x Full-height, Full-length PCI expansion slots

Drive Bays

- Hot-swap • 8x 3.5" SAS / SATA Hot-swap Drive Bays
- Peripheral Bay(s) • SAS or enterprise SATA HDD only recommended
- 2x 5.25" Peripheral Drive Bay
- 1x 5.25" Bay For 3.5" Device
- Drive Bays are 90° Rotatable

SAS / SATA Backplane

SAS / SATA Hard Drive Backplane w/AMI MG9072

Front Panel

- Buttons • Power On/Off button
- System Reset button
- Power LED
- Hard drive activity LED
- LEDs • 2x Network activity LEDs
- System Overheat LED
- Power Fail LED
- Ports • 2x USB Ports

Exception caught! Variable PRODID is undefined.
System Cooling

- Fans • 4x 5000 RPM Hot-swap PWM Cooling Fans

System Monitoring

Chassis intrusion switch

Operating Environment (System)

- Operating Temperature Range • 5°C ~ 35°C (41°F ~ 95°F)
- Non-Operating Temperature Range • -40°C ~ 60°C (-40°F ~ 140°F)
- Operating Relative Humidity Range • 8% ~ 90% (non-condensing)
- Non-Operating Relative Humidity Range • 5% - 95% (non-condensing)

Power Supply

- 865W AC power supply (cooling-redundant) w/ PFC
- AC Voltage • 100 - 240V, 50-60Hz, 12-6 Amp
- +5V standby • 6.5 Amp
- +12V • 70 Amp
- +5V • 30 Amp
- +3.3V • 30 Amp
- 12V • 1 Amp

Certification



[Certified](#)

Regulatory (Power Supply)

- Power Supply Safety / EMC • USA - UL listed, FCC
- Canada - CUL listed
- Germany - TUV Certified
- Europe/CE Mark
- EN 60950/IEC 60950-Compliant

