

Supermicro MBD-X10SRW-F, Single SKT, Intel C612 Chipset, SATA, 2xGbE, IPMI Bulk

Kod producenta: MBD-X10SRW-F-B



Form Factor	Proprietary
Dimensions	8.15" x 13.05"
CPU Socket	LGA 2011 (Socket R3)
# of CPU sockets	1
Supported CPU's	Intel Xeon E5-2600v4 Intel Xeon E5-2600v3 Intel Xeon E5-1600v4 Intel Xeon E5-1600v3
Chipset	Intel C612 Wellsburg
Memory Type	DDR4 ECC 3DS LRDIMM DDR4 ECC LRDIMM DDR4 ECC RDIMM
Memory Speed	2400 MHz 2133 MHz 1866 MHz 1600 MHz
# of DIMM's	8
Max Memory Size	1024 GB
Integrated GPU	Aspeed AST2400
# of PCIe x8 3.0	1
# of USB Ports	2 x USB 3.0 (rear) 1 x USB 3.0 (header) 1 x USB 3.0 Type A 2 x USB 2.0 (rear) 6 x USB 2.0 (header)
# of SATA Ports	10
Storage Controllers	6 x AHCI iSATA 6Gb/s 4 x sSATA 6Gb/s
Integrated RAID	0,1,5,10
# of Serial Ports	1 x Fast UART 16550 (rear) 1 x Fast UART 16550 (header)
# of 1GbE Ports	2 x RJ45
Network Controllers	Intel i350 Dual Port Gigabit Ethernet
Integrated BMC	IPMI 2.0 KVM-over-LAN Virtual Media over LAN IPMI Dedicated RJ45 PHY
BMC chip	Aspeed AST2400
TPM	1 x TPM 1.2 20-pin Header
Uwagi	PCI-Express Slots Configuration: 1x PCI-E 3.0 x8 (in x16) slot Riser card support:1x PCI-E 3.0 x32 Left side

Product SKUs		Chassis (Optimized for X10SRW-F)	
MBD-X10SRW-F-B		• X10SRW-F (Bulk Pack)	
Physical Stats		1U Chassis:	
Form Factor • Proprietary		- SC815TQ-600WB	
Dimensions • 8.15" x 13.05", (20.70cm x 33.15cm)		- SC113TQ-600WB	
		- SC113TQ-R700WB	
		- SC116AC-R700WB	
		- SC815TQ-R706WB	
		- SC514-R400W	
		- SC116TQ-R700WB	
		- SC213A-R740WB	
		- SC826BA-R920WB	
		- SC825TQ-R740WB	
		- SC825TQ-R500WB	
Processor		2U Chassis:	
CPU		- Intel® Xeon® processor E5-2600 v4/v3, E5-1600 v4/v3 family (up to 145W TDP **)	
		- Single Socket R3 (LGA 2011)	
Core / Cache		- Up to 22 Cores / Up to 55MB Cache	
Note		BIOS version 2.0 or above is required	
		** Motherboard supports this maximum TDP. Please verify your system can thermally support	
Note		** E5-1600 series CPU does not support LRDIMM type memory	
System Memory		SuperServer(s) with X10SRW-F	
		- SYS-1018R-WR	
		- SYS-1018R-WCQR	
		- SYS-5028R-WR	
		- SYS-5018R-WR	
Memory Capacity		Expansion Slots	
- 8x 288-pin DDR4 DIMM slots		- SYS-1018R-WR	
- Up to 1TB ECC 3DS LRDIMM		- SYS-1018R-WCQR	
- Up to 512GB ECC LRDIMM		- SYS-5028R-WR	
- Up to 256GB ECC RDIMM		- SYS-5018R-WR	
- 2400 / 2133/1866/1600MHz ECC			
Memory Type		PCI-Express	
DDR4 SDRAM 72-bit, 288-pin (RDIMM / LRDIMM) / 284-pin gold-plated DIMMs		- 1x PCI-E x8 3.0 (in x16) slots	
		- 1x PCI-E x8 3.0 x32 Left Riser slot	
DIMM Sizes		System BIOS	
- 3DS LRDIMM: 128GB		BIOS Type	
- LRDIMM: 64GB, 32GB		- 128Mb SPI Flash EEPROM with AMI BIOS	
- RDIMM: 32GB, 16GB, 8GB, 4GB		- Play and Play (PaP)	
Memory Voltage		- APM 1.2	
- 1.2 V		- DMI 2.3	
Error Detection		- PCI 2.3	
- Corrects single-bit errors		- ACPI 1.0 / 2.0 / 3.0 / 4.0	
- Detects double-bit errors (using ECC Memory)		BIOS Features	
		- USB Keyboard support	
		- Hardware BIOS Virus protection	
		- SMBIOS 2.7.1	
		- UEFI 2.3.1	
		- RTC (Real Time Clock) Wakeup	
On-Board Devices		Management	
Chipset		- IPMI 2.0 with KVM support	
SATA		- SuperDoctor® 5	
- SATA3 (6Gbps) via C612 controller		- Watch Dog	
- RAID 0, 1, 5, 10 support		- ACPI Power Management	
- Support for Intel® Virtualization Platform Management Interface v2.0		- Keyboard Wakeup from Soft-Off	
IPMI		Power Configurations	
- IPMI 2.0 with virtual media over LAN and KVM-over-LAN support		- CPU Fan Auto-off in sleep mode	
- ASPEED AST2400 BMC		- Power-on mode for AC power recovery	
Network Controllers		PC Health Monitoring	
Ethernet		- Monitors for CPU Cores, +3.3V, +5V, +12V, +5V Standby, VBAT, HT, Memory, Chipset Voltages.	
- Supports 10BASE-T, 100BASE-TX, and 1000BASE-T, RJ45 output		- Total of 6 fan headers supporting up to 6 fans	
Graphics		- 6 fans with tachometer status monitoring	
- ASPEED AST2400 BMC		- Status monitor for speed control	
		- Status monitor for on/off control	
		- Low noise fan speed control	
		- Pulse Width Modulated (PWM) fan connectors	
		- Monitoring for CPU and chassis environment	
		- CPU thermal trip support	
		- FC temperature sensing logic	
		- Thermal Monitor 2 (TM2) support	
		- PECI	
		- CPU / System Overheat LED	
		- Suspend static indicator LED	
		- UID/Remote UID	
		- Chassis intrusion detection	
		- Chassis intrusion header	
		- Chipkill support	
		- RoHS, Halogen Free	
OS Compatibility		Operating Environment	
• Please reference the OS Compatibility Chart for details		Operating Temperature Range	
		- 0°C ~ 60°C (32°F ~ 140°F)	
		Non-Operating Temperature Range	
		- -20°C ~ 60°C (-4°F ~ 140°F)	
		Operating Relative Humidity Range	
		- 10% ~ 85% (non-condensing)	
		Non-Operating Relative Humidity Range	