

Supermicro SuperChassis 216BE1C-R741JBOD 2U 24xSFF 12G SAS/SATA SGL EXP 740W 1+1

Kod producenta: CSE-216BE1C-R741JBOD



Form Factor	Rack 2U
Host Interface	SAS 12Gbps
HDD Interface	SAS3, SATA3
SAS Expander	Single
Management	IPMI RJ45 port
Hot-swap 2.5" bays	24
Connectors	4 x SFF-8644
PSU	Redundant
Dimensions	437 x 89 x 630mm
PSU Wattage	740W
Rack Rails	included

Product SKUs



CSE-216BE1C-R741JBOD • SuperChassis
216BE1C-R741JBOD

Form Factor



• 2U JBOD storage chassis

Dimensions



Height - 3.5" (89 mm)
Width - 17.2" (437 mm)
Depth - 24.8" (630 mm)
Net Weight - 55 lbs (24.95 kg)
Gross Weight - 60 lbs (27.22 kg)
Packaging - 26.7" (678 mm) x 11.4" (290 mm)
(W x H x L) x 34.5" (876 mm)
Available - Black
Color

Drive Bays



- 24 x 2.5" hot-swap HDD bay for JBOD solution

Backplane



- 24-port 2U SAS3 12Gbps single-expander backplane, support up to 24x 2.5-inch SAS3/SATA3 HDD/SSD

Front Panel



Buttons - Power On/Off button
- System Reset Button
- Unit Identification (UID) button
LEDs - 1 Network Activity LEDs

Systems Cooling



Fans - 3 x 80x38mm hot-swap cooling fan(s)

System Monitoring



- IPMI

Operating Environment (System)



Operating Temperature - 5°C - 35°C (41°F - 95°F)
Range
Non-Operating Temperature - -40°C - 70°C (-40°F - 158°F)
Range
Operating Relative Humidity - 8% - 90% (non-condensing)
Range
Non-Operating Relative Humidity - 5% - 95% (non-condensing)
Range

Power Supply

1U 740W Redundant Platinum Power Supply W/PMbus

Power Efficiency - 94%

Total Output Power and Input - 740W with Input 100 - 240Vac

AC Input Frequency - 50-60Hz

Dimensions (L x W x H) - 346 x 76 x 40 mm

Output Type - Backplanes (gold finger)

+12V - Max: 61.7A / Min: 0.2A (100Vac - 240Vac)

+5Vsb - Max: 4A / Min: 0A

- PDB-PT216-2824

- O/P: 12V/100

Power Distributor - +5V Max: 30

- +3.3V Max: 24

- -12V Max: 0.6

Certification -  **Platinum Certified**

Regulatory (Power Supply)



- BSMI

Power Supply - CCC

- FCC class A

Safety / EMC - TUV/CB

Strona firmowa produktu:

<https://www.superstorage.pl/supermicro-superchassis-216be1c-r741jbod-2u-24xsff-12g-sassata-sgl-exp-740w-11-p-2920.html>