

Supermicro MBD-X11SAT, Single SKT, Intel C236 Chipset, SATA, 2xGbE,M.2 Bulk

Part number: MBD-X11SAT-B



Category	Workstation
Form Factor	ATX
Dimensions	12" x 9.6"
CPU Socket	LGA 1151 (Socket H4)
# of CPU sockets	1
Supported CPU's	Intel Xeon E3-1200v5 Intel Xeon E3-1200v6 Intel Core 7th Gen. Intel Core 6th Gen.
Chipset	Intel C236 Skylake
Memory Type	DDR4 ECC UDIMM DDR4 non-ECC UDIMM
Memory Speed	2400 MHz 2133 MHz 1866 MHz 1600 MHz
# of DIMM's	4
Max Memory Size	64 GB
# of PCIe x16 3.0	3
# of USB Ports	1 x USB 3.1 (rear) 2 x USB 3.0 (rear) 4 x USB 3.0 (header) 2 x USB 2.0 (rear) 2 x USB 2.0 (header)
# of SATA Ports	6
Storage Controllers	6 x AHCI iSATA 6Gb/s
Integrated RAID	0,1,5,10
# of Serial Ports	1 x Fast UART 16550 (header)
# of 1GbE Ports	2 x RJ45
Network Controllers	Intel i219LM Port Gigabit Ethernet Intel i210AT Port Gigabit Ethernet
TPM	1 x TPM 1.2 20-pin Header

Product SKUs		Expansion Slots	
<input type="checkbox"/>	MBD-X11SAT • X11SAT (Bulk Pack)	<input type="checkbox"/>	<ul style="list-style-type: none"> • 3 PCI-E 3.0 x16 • 1 PCI-E 3.0 x1 • 1 - 5V PCI 32bit • ***3 PCIe16 slots are running at 16/NA/16 or 16/8/8.*** **PCIe x1 is in x4 slot***
Physical Stats		PCI-E	
<input type="checkbox"/>	Form Factor • ATX		
	Dimensions • 12" x 9.6" (30.48cm x 24.38cm)		
Processor/Cache		System BIOS	
<input type="checkbox"/>		<input type="checkbox"/>	
	<ul style="list-style-type: none"> • Intel® 6th/7th Generation Core™ i3 series • Intel® 6th/7th Generation Core™ i5 series • Intel® 6th/7th Generation Core™ i7 series • Intel® Xeon® Processor E3-1200 v6/v5 series • Socket H4 (LGA 1151) supported; CPU TDP support Up to 95W TDP • BIOS version 2.0 or above is required to support 7th Generation Intel® Core™ i3 Processors and Intel® Xeon® Processor E3-1200 v6 series 	BIOS Type	<ul style="list-style-type: none"> • AMI UEFI • Plug and Play (PnP) • DMI 2.3 • PCI 3.0 • ACPI 5.0
CPU		BIOS Features	<ul style="list-style-type: none"> • USB Keyboard support • Hardware BIOS Virus protection • SMBIOS 3.0 • UEFI 2.3.1 • RTC (Real Time Clock) Wakeup
Note		Management	
		<input type="checkbox"/>	
		Software	<ul style="list-style-type: none"> • AMT • SuperDoctor® 5 • vPro • Watchdog • ACPI Power Management • Keyboard Wakeup from Soft-Off
System Memory		Power Configurations	<ul style="list-style-type: none"> • CPU Fan auto-off in sleep mode • Power-on mode for AC power recovery
<input type="checkbox"/>			
Memory Capacity	<ul style="list-style-type: none"> • Up to 64GB Unbuffered ECC/non-ECC UDIMM, DDR4-2400MHz, in 4 DIMM slots 	PC Health Monitoring	
Memory Type	<ul style="list-style-type: none"> • 2400/2133/1866/1600MHz ECC DDR4 SDRAM 72-bit, 288-pin (UDIMM) gold-plated DIMMs 	<input type="checkbox"/>	
DIMM Sizes	<ul style="list-style-type: none"> • 4GB, 8GB, 16GB 	Voltage	<ul style="list-style-type: none"> • +12V, +3.3V, +5V, +5V standby, Chassis intrusion header, Monitors CPU voltages, VBAT
Memory Voltage	<ul style="list-style-type: none"> • 1.2V 	FAN	<ul style="list-style-type: none"> • 5x 4-pin fan headers (up to 5 fans) • Fan speed control • Overheat LED indication • CPU thermal trip support • I2C temperature sensing logic
Error Detection	<ul style="list-style-type: none"> • Corrects single-bit errors • Detects double-bit errors (using ECC memory) 	Temperature	<ul style="list-style-type: none"> • PECI • Thermal Monitor 2 (TM2) support • CPU / System Overheat LED • Suspend static indicator LED • UID/Remote UID • 8-pin 12v DC power connector • ATX Power connector • Control of power-on for recovery from AC power loss
On-Board Devices		Other Features	<ul style="list-style-type: none"> • CPU thermal trip support for processor protection • Intel Smart Response Technology • WOL
<input type="checkbox"/>			
Chipset	<ul style="list-style-type: none"> • Intel® C236 • Intel® C236 controller for 6 SATA3 (6 Gbps) ports; RAID 0,1,5,10 	LED	
SATA	<ul style="list-style-type: none"> • + 1 PCIe M.2(PCIe x4, 2242/2260/2280)(No Raid Support) • Single Intel® Ethernet Controller I210-AT 		
Network Controllers	<ul style="list-style-type: none"> + Single Intel Ethernet PHY i219LM 		
Audio	<ul style="list-style-type: none"> • ALC 888S HD Audio 		
Input / Output			
<input type="checkbox"/>			
USB	<ul style="list-style-type: none"> • 4 USB 2.0 ports (2 rear, 2 via header(s)) • 6 USB 3.0 ports (2 rear, 4 via header(s)) • 1 USB 3.1 (10 Gb/s) Type C ports (Rear, share with Thunderbolt and Display port) 		
Video Output	<ul style="list-style-type: none"> • 1 DVI - D port(s), 1 DP (DisplayPort) port(s), 1 HDMI port(s) 		
Serial Port / Header	<ul style="list-style-type: none"> • 1 COM Port (1 header(s)) 		
TPM	<ul style="list-style-type: none"> • 1 TPM 2.0 Header 		
Others	<ul style="list-style-type: none"> • Support Thunderbolt(USB3.1 only,Full Thunderbolt functions need to do firmware update to enable that will be only posted to Supermicro web site after Intel released dedicated ID to Supermicro.) 		

Visit us for more info:

<https://www.superstorage.pl/supermicro-mbd-x11sat-single-skt-intel-c236-chipset-sata-2xgbem2-bulk-p-2988.html>