

Supermicro SuperServer SYS-1029U-E1CRTP2 1U DP 10xSFF 2xGbE 2x10GbE SFP+ RED PSU

Kod producenta: SYS-1029U-E1CRTP2



Chassis Form Factor	Rack 1U
CPU Socket	LGA 3647 (Socket P)
# of CPU sockets	2
Supported CPU's	Intel Xeon Scalable Processors
Max CPU TDP	205 W
Chipset	Intel C621
Memory Type	DDR4 ECC 3DS LRDIMM DDR4 ECC RDIMM
Memory Speed	2666 MHz 2400 MHz 2133 MHz
# of DIMM's	24
Max Memory Size	3072 GB
Integrated GPU	Aspeed AST2500
# of 2.5 hot-swap bays	10
# of PCIe x16 3.0	2
# of PCIe x8 3.0	2
# of USB Ports	2 x USB 3.0 (rear) 2 x USB 3.0 (header) 1 x USB 3.0 Type A
# of SATA Ports	10
Storage Controllers	10 x AHCI iSATA 6Gb/s
Integrated RAID	0,1,5,10
# of Serial Ports	1 x Fast UART 16550 (header)
# of 10GbE Ports	2 x SFP+
# of 1GbE Ports	2 x RJ45
Network Controllers	Intel i350-AM2 Port Gigabit Ethernet Intel X710-AM2 Port Gigabit Ethernet
Integrated BMC	IPMI 2.0 KVM-over-LAN Virtual Media over LAN IPMI Dedicated RJ45 PHY
BMC chip	Aspeed AST2500
Power Supply	Redundant
PSU Wattage	750W
PSU Certification	80+ Platinum
Chassis Dimensions	437 x 43 x 724mm
Uwagi	HDD bays configuration: 10x SAS3 ports support (SAS Add-on card is opt.) Network Connectivity 2x 10G SFP+ ports AOC-URN2-I4GXS-O (Intel X710-AM2 and Intel i350-AM2)

Poniżej prezentujemy szczegółowy opis techniczny oferowanego produktu:

UWAGA !!!

Ze względu na wysoki stopień integracji platforma dostępna jest tylko i wyłącznie jako gotowy system wraz z CPU, RAM i HDD oraz dodatkowymi kartami rozszerzeń. Prosimy o kontakt z nami w celu przedstawienia oferty na interesującą Państwa konfigurację.

