

Supermicro SuperChassis SC732D4-500B Mid-Tower 4xLFF FIX PSU

Kod producenta: CSE-732D4-500B



Chassis Form Factor	Mid-Tower
# of 3.5 fixed bays	4
Power Supply	Fixed
PSU Wattage	500W
PSU Certification	80+ Bronze
Chassis Dimensions	424 x 193 x 525mm

Poniżej prezentujemy szczegółowy opis techniczny oferowanego produktu:

Product SKUs
CSE-732D4-500B • SuperChassis 732D4-500B

Form Factor
• Mid-tower chassis support for max. motherboard size - 12" x 13" E-ATX, 12" x 10" ATX and 9.6" x 9.6" Micro-ATX

Processor Support
• Dual, single Intel® / AMD processors

Dimensions
Height - 16.7" (424 mm)
Width - 7.6" (193 mm)
Depth - 20.68" (525 mm)
Net Weight - 28 lbs (12.7 kg)
Gross Weight - 30 lbs (13.61 kg)
Packaging (W x H x L) - 21.38" (543 mm) x 11.97" (304 mm) x 25.28" (642 mm)
Available Color - Black

Expansion Slots
- 7 full-height & full-length expansion slot(s)

Drive Bays
- 4 x 3.5" fixed drive bay
- Optional 4 x 2.5" fixed drive bay

Peripheral Drives
- 2 x standard 5.25" drive bay
- 1 x 3.5" internal fixed drive bay

Front Panel
Buttons - Power On/Off button
- 1 Network Activity LEDs
LEDs - HDD activity LED
- Power Status LED
- System Overheat LED
Ports - 2x USB 3.0 Port(s)
- 2x USB 2.0 Port(s)
- 2x HD/AC97 Audio port(s)

Motherboard (for CSE- 732D4-500B)
X9DAL-3 X9DAL-i
X9SAE X9SAE-V
X9SCV-Q X10SLQ
X10SL7-F X10SLM+-LN4F
X10SLM+-F X10SLH-F
X10SLM-F X10SLF-F
X10SLL-S X10SLL-SF
X10SLA-F X10SLL+-F
X10SAE C7Z87-OCE
X10SAT X10SLQ-L
X11SSQ X11SAE
X11SAE-F X11SAE-M
X11SAT-F X11SSQ-L
C7Z270-CG C7H270-CG-ML
C7Z270-PG C7Z270-CG-L
C7Q270-CB-ML C7B250-CB-ML

Servers (for CSE- 732D4-500B)
5039A-iL

Systems Cooling
- 1 x 12cm rear exhaust fan(s)
Fans - Optional 1 x 12cm (front) cooling fan

Operating Environment (System)
Operating Temperature - 5°C - 35°C (41°F - 95°F)
Range
Non-Operating Temperature - -40°C - 70°C (-40°F - 158°F)
Range
Operating Relative Humidity - 8% - 90% (non-condensing)
Range
Non-Operating Relative Humidity - 5% - 95% (non-condensing)
Range

Power Supply
PS2/ATX 500W Multi-output power supply with 12CM fan, Bronze level
Power Efficiency - 88%
Total Output Power and Input - 500W with Input 100 - 240Vac
AC Input Frequency - 50-60Hz
Dimensions (L x W x H) - 140 x 150 x 86 mm
Output Type - 24pin ATX
-12V - Max: 0.5A / Min: 0A
- Max: 17A / Min: 1A (100Vac - 240Vac)
+12V - Max: 17A (100Vac - 240Vac)
- Max: 17A (100Vac - 240Vac)
+5V - Max: 20A / Min: 0.5A
+3.3V - Max: 15A / Min: 0.5A
+5Vsb - Max: 3A / Min: 0A
Certification - **Bronze Certified**

Regulatory (Power Supply)
Power Supply Safety / EMC - CE/EMC
- FCC class B
- TUV/CB

Strona firmowa produktu:

<https://www.superstorage.pl/supermicro-superchassis-sc732d4-500b-mid-tower-4xlff-fix-psu-p-3494.html>