

Supermicro SuperChassis SC733TQ-668B Mid-Tower 4xLFF FIX PSU

Kod producenta: CSE-733TQ-668B



Chassis Form Factor	Mid-Tower
# of 3.5 hot-swap bays	4
Power Supply	Fixed
PSU Wattage	668W
PSU Certification	80+ Platinum
Chassis Dimensions	426 x 178 x 531mm

Poniżej prezentujemy szczegółowy opis techniczny oferowanego produktu:

Product SKUs



CSE-733TQ-668B • SuperChassis 733TQ-668B

Form Factor



- Mid-tower chassis - supports for maximum motherboard sizes: 12" x 13" E-ATX and ATX

Processor Support



- Dual and Single Intel® and AMD processors

Dimensions



- Height - 16.8" (426 mm)
- Width - 7" (178 mm)
- Depth - 20.9" (531 mm)
- Net Weight - 38 lbs (17.24 kg)
- Gross Weight - 40 lbs (18.14 kg)
- Packaging (W x H x L) - 24.2" (615 mm) x 11.8" (300 mm) x 26.4" (671 mm)
- Available Color - Black

Expansion Slots



- 7 full-height & full-length expansion slot(s)

Drive Bays



- 4 x 3.5" hot-swap SAS/SATA drive bay with SGPIO

Backplane



- 4x3.5" SAS2/SATA3 backplane w/SES-II

Peripheral Drives



- 2 x standard 5.25" drive bay
- 1 x 3.5" internal fixed drive bay

Front Panel



- Buttons
 - Power On/Off button
 - System Reset Button
 - 1 Network Activity LEDs
- LEDs
 - HDD activity LED
 - Power LED
 - System Overheat LED

Ports - 2x USB 2.0 Port(s)

Systems Cooling



- Fans
 - 1 x 12cm rear exhaust fan(s)
 - 1 x 9cm hot-swap cooling fan(s)

Operating Environment (System)



- Operating Temperature Range - 5°C - 35°C (41°F - 95°F)
- Non-Operating Temperature Range - -40°C - 70°C (-40°F - 158°F)
- Operating Relative Humidity Range - 8% - 90% (non-condensing)
- Non-Operating Relative Humidity Range - 5% - 95% (non-condensing)

Power Supply

- PS2 668W Multi-output power supply 80PLUS Platinum
- Power Efficiency - 92%
- Total Output Power and Input - 668W with Input 100 - 240Vac
- AC Input Frequency - 50-60Hz
- Dimensions (L x W x H) - 185 x 150 x 86 mm
- Output Type - 24pin ATX
- 12V - Max: 0.1A / Min: 0A
- +12V - Max: 54A / Min: 0.2A (100Vac - 240Vac)
- +5V - Max: 11.8A / Min: 0.1A
- +3.3V - Max: 12A / Min: 0.1A
- +5Vsb - Max: 2A / Min: 0A
- Certification - **Platinum Certified**

Regulatory (Power Supply)



- BSMI
- Power Supply Safety / EMC
 - CCC
 - CE/EMC
 - FCC class B
 - TUV/CB
 - UL/CUL

Strona firmowa produktu:

<https://www.superstorage.pl/supermicro-superchassis-sc733tq-668b-mid-tower-4xlff-fix-psu-p-3495.html>