

Supermicro SuperChassis SC813MF2TQC-R608CB 1U 4xLFF RED PSU

Kod producenta: CSE-813MF2TQC-R608CB



Chassis Form Factor	Rack 1U
# of 3.5 hot-swap bays	4
Power Supply	Redundant
PSU Wattage	600W
PSU Certification	80+ Platinum
Chassis Dimensions	437 x 43 x 507mm

Poniżej prezentujemy szczegółowy opis techniczny oferowanego produktu:

Product SKUs

CSE-813MF2TQC-R608CB • SuperChassis
813MF2TQC-R608CB

Form Factor

- 1U chassis, support motherboard sizes: ATX 12" x 10" and Micro ATX 9.6" x 9.6"

Processor Support

- Dual and Single Intel® and AMD processors

Dimensions

Height	- 1.7" (43 mm)
Width	- 17.2" (437 mm)
Depth	- 19.98" (507 mm)
Gross Weight	- 33.5 lbs (15.2 kg)
Packaging (W x H x L)	- 23.4" (594 mm) x 8.5" (216 mm) x 29.7" (754 mm)
Available Color	- Black

Expansion Slots

- 1 full height expansion slot(s)

Drive Bays

- 4 x 3.5" hot-swap SAS/SATA
- SAS or enterprise SATA HDD only recommended

Backplane

- 1U 4-Port 12Gbps Backplane Support 4x3.5" SAS3/SATA3 HDD/SSD

Peripheral Drives

- 1 x slim DVD-ROM drive bay
- Optional 1 x USB + COM port tray

Front Panel

Buttons	- Power On/Off button - System Reset Button - 2 Network Activity LEDs
LEDs	- HDD activity LED - Power Status LED - System Information LED

Motherboard (for CSE- 813MF2TQC-R608CB)

[X11DPL-i](#)

Servers (for CSE- 813MF2TQC-R608CB)

[6019P-MTR](#)

Systems Cooling

Fans	- 4 x 40x28mm PWM fan(s) - Optional 2 x fans for AOC cooling
------	---

Operating Environment (System)

Operating Temperature Range	- 5°C - 35°C (41°F - 95°F)
Non-Operating Temperature Range	- -40°C - 70°C (-40°F - 158°F)
Operating Relative Humidity Range	- 8% - 90% (non-condensing)
Non-Operating Relative Humidity Range	- 5% - 95% (non-condensing)

Power Supply

1U 600W redundancy PWS meet PMBus 1.2 with high efficiency and high power density

Total Output Power and Input	- 600W with Input 100 - 240Vac
AC Input Frequency	- 50-60Hz
Dimensions (L x W x H)	- 220 x 54.5 x 40.25 mm
Output Type +12V +5Vsb	- Backplanes (gold finger) - Max: 50A (100Vac - 240Vac) - Max: 3A - PDB-PT813M-2424 - O/P: 120/62
Power Distributor	- +5V Max: 25 - +3.3V Max: 25 - -12V Max: 0.6
Certification	- 80 Plus Platinum (high-efficiency)

Regulatory (Power Supply)

Power Supply Safety / EMC	- BSMI - CCC - UL/CB
---------------------------	----------------------------

Strona firmowa produktu:

<https://www.superstorage.pl/supermicro-superchassis-sc813mf2tqc-r608cb-1u-4x1ff-red-psu-p-3561.html>