

Supermicro SuperChassis SC826BE1C4-R1K23LPB 2U 12xLFF RED PSU

Kod producenta: CSE-826BE1C4-R1K23LPB



Chassis Form Factor	Rack 2U
# of 3.5 hot-swap bays	12
Power Supply	Redundant
PSU Wattage	1200W
PSU Certification	80+ Titanium
Chassis Dimensions	437 x 89 x 647mm

Product SKUs	
CSE-826BE1C4-R1K23LPB • SuperChassis 826BE1C4-R1K23LPB	
Form Factor	
• 2U chassis support max. motherboard size - ATX 12" x 10", E-ATX 12" x 13", EE-ATX 13" x 13.68". • Support up to ATX 12"x13" MB with rear 2.5" HDD option installed	
Processor Support	
• Dual and Single Intel® and AMD processors	
Dimensions	
Height	- 3.5" (89 mm)
Width	- 17.2" (437 mm)
Depth	- 25.5" (647 mm)
Gross Weight	- 55 lbs (24.95 kg)
Packaging (W x H x L)	- 26.7" (678 mm) x 11.4" (290 mm) x 34.5" (876 mm)
Available Color	- Black
Expansion Slots	
- 7 low-profile expansion slot(s)	
Drive Bays	
- 12 x 3.5" hot-swap SAS/SATA drive bay with SES3 - Optional 2 x 2.5" hot-swap drive bay	
Backplane	
- 12-port 2U SAS3 12Gbps single-expander backplane, support up to 8x 3.5-inch SAS3/SATA3 HDD/SSD and 4x NVMe/SAS3/SATA3 storage devices	
Front Panel	
Buttons	- Power On/Off button - System Reset Button - 2 Network Activity LEDs - Fan Fail/System Over Heat LED
LEDs	- HDD activity LED - Power Status LED - Unit Identification (UID) LED

Motherboard (for CSE- 826BE1C4-R1K23LPB)	
H11DSI-NT	X11DPH-T
X11DPH-I	X11DPH-TQ
H11DSi	
Servers (for CSE- 826BE1C4-R1K23LPB)	
6029P-E1CR12H	6029P-E1CR12L
6029P-E1CR12T	
Systems Cooling	
Fans	- 3 x 8cm high-performance PWM fan(s)
System Monitoring	
- Chassis intrusion switch	
Operating Environment (System)	
Operating Temperature Range	- 5°C - 35°C (41°F - 95°F)
Non-Operating Temperature Range	- -40°C - 70°C (-40°F - 158°F)
Operating Relative Humidity Range	- 8% - 90% (non-condensing)
Non-Operating Relative Humidity Range	- 5% - 95% (non-condensing)
Power Supply	
1U 1200W/1000W Titanium Power Supply W/PMbus W76xL360xH40mm	
Power Efficiency	- 96%
Total Output	- 1000W with Input 100 - 127Vac
Power and Input	- 1200W with Input 200 - 240Vac - 1200W with Input 200 - 240Vdc
AC Input Frequency	- 50-60Hz
Dimensions (L x W x H)	- 336 x 76 x 40 mm
Output Type	- Backplanes (gold finger) - Max: 83A (100Vac - 127Vac) - Max: 100A (200Vac - 240Vac) - Max: 100A (200 - 240)
+12V	- Max: 4A / Min: 0A
+5Vsb	- PDB-PT826-8824 - O/P: 12V/135A - +5V Max: 40A - +3.3V Max: 24A - -12V Max: 0.6A
Power Distributor	
Certification	- Titanium Certified
Regulatory (Power Supply)	
- BSMI - CCC - CE/EMC - FCC class A - UL/CB - UL/CUL	

Strona firmowa produktu:

<https://www.superstorage.pl/supermicro-superchassis-sc826be1c4-r1k23lpb-2u-12xlff-red-psu-p-3609.html>