

Supermicro SuperChassis SC826BAC4-R1K23WB 2U 12xLFF RED PSU

Kod producenta: CSE-826BAC4-R1K23WB



Chassis Form Factor	Rack 2U
# of 3.5 hot-swap bays	12
Power Supply	Redundant
PSU Wattage	1200W
PSU Certification	80+
Chassis Dimensions	437 x 89 x 647mm
Uwagi	12-port 2U SAS3 12Gb/s hybrid backplane, support up to 8x 3.5-inch SAS3/SATA3 HDD/SSD and 4x SAS3/SATA3/NVMe Storage Devices

Product SKUs

CSE-826BAC4-R1K23WB • SuperChassis 826BAC4-R1K23WB

Motherboard (for CSE- 826BAC4-R1K23WB)

X11DDW-L

X11DDW-NT

Form Factor

• 2U chassis support for SMC Proprietary WIO motherboards max. motherboard size - 12" x 13", 13" x 13.68".

• Support up to 12"x13" MB with rear 2.5" HDD option installed

Servers (for CSE- 826BAC4-R1K23WB)

6029P-WTRT

Processor Support

• Dual and Single Intel® and AMD processors

Dimensions

Height

Width

Depth

Net Weight

Gross Weight

Packaging (W x H x L)

Available Color

- 3.5" (89 mm)

- 17.2" (437 mm)

- 25.5" (647 mm)

- 40 lbs (18.14 kg)

- 55 lbs (24.95 kg)

- 26.7" (678 mm) x 11.4" (290 mm) x 34.5" (876 mm)

- Black

Expansion Slots

- WIO Slots (4x Full-height, Half-length + 3x Low-profile)

Drive Bays

- 12 x 3.5" hot-swap drive bay

- Optional 2 x 2.5" hot-swap drive bay

- 8x SAS3 12Gbps and 4x Hybrid (NVMe/SAS3) 3.5" HDD

Backplane

- 12-port 2U SAS3 12Gbps hybrid backplane, support up to 8x 3.5-inch SAS3/SATA3 HDD/SSD and 4x SAS3/SATA3/NVMe Storage Devices

Front Panel

Buttons

LEDs

- Power On/Off button

- System Reset Button

- 2 Network Activity LEDs

- Fan Fail/System Over Heat LED

- HDD activity LED

- Power Status LED

- Unit Identification (UID) LED

Systems Cooling

- 3 x 8cm high-performance PWM fan(s)

- Optional 5 x 6cm 4pin high performance fan(s)

System Monitoring

- Chassis intrusion switch

Operating Environment (System)

Operating Temperature Range

Non-Operating Temperature Range

Operating Relative Humidity Range

Non-Operating Relative Humidity Range

- 5°C - 35°C (41°F - 95°F)

- -40°C - 70°C (-40°F - 158°F)

- 8% - 90% (non-condensing)

- 5% - 95% (non-condensing)

Power Supply

1U 1200W/1000W Titanium Power Supply W/PMbus W76xL360xH40mm

Power Efficiency

Total Output Power and Input

AC Input Frequency

Dimensions (L x W x H)

Output Type

+12V

+5Vsb

Power Distributor

- 96%

- 1000W with Input 100 - 127Vac

- 1200W with Input 200 - 240Vac

- 1200W with Input 200 - 240Vdc

- 50-60Hz

- 336 x 76 x 40 mm

- Backplanes (gold finger)

- Max: 83A (100Vac - 127Vac)

- Max: 100A (200Vac - 240Vac)

- Max: 100A (200 - 240)

- Max: 4A / Min: 0A

- PDB-PT826-S8824

- O/P: 12V/135A

- +5V Max: 40A

- +3.3V Max: 24A

- -12V Max: 0.6A

Certification

- Titanium Certified

Regulatory (Power Supply)

Power Supply Safety / EMC

- BSMI

- CCC

- CE/EMC

- FCC class A

- UL/CB

Strona firmowa produktu:

<https://www.superstorage.pl/supermicro-superchassis-sc826bac4-r1k23wb-2u-12xlff-red-psu-p-3610.html>