

Supermicro SuperStorage Server SSG-6029P-E1CR12T 2U DP 12xLFF LSI 3108 2x10GbE RED PSU

Kod producenta: SSG-6029P-E1CR12T

	Chassis Form Factor	Rack 2U
	CPU Socket	LGA 3647 (Socket P)
	# of CPU sockets	2
	Supported CPU's	Intel Xeon Scalable 2nd Gen Intel Xeon Scalable 1stt Gen
	Max CPU TDP	205 W
	Chipset	Intel C624
	Memory Type	DDR4 ECC LRDIMM DDR4 ECC RDIMM
	Memory Speed	2666 MHz 2400 MHz 2133 MHz
	# of DIMM's	16
	Max Memory Size	2048 GB
	Integrated GPU	Aspeed AST2500
	# of 3.5 hot-swap bays	12
	# of PCIe x16 3.0	3
	# of PCIe x8 3.0	4
	# of USB Ports	4 x USB 3.0 (rear) 1 x USB 3.0 Type A
	# of SATA Ports	10
	# of SAS Ports	8
	Storage Controllers	8 x AHCI iSATA 6Gb/s 2 x sSATA 6Gb/s LSI 3108 12Gb/s AOC
	Integrated RAID	0,1,5,10
	Hardware RAID	0,1,5,6,10,50,60
	# of Serial Ports	1 x Fast UART 16550 (header)
	# of 10GbE Ports	2 x RJ45
	Network Controllers	Intel x722 Port 10 Gigabit Base-T Intel x557 Port 10 Gigabit Base-T
	Integrated BMC	IPMI Dedicated RJ45
	BMC chip	Aspeed AST2500
	TPM	1 x TPM 1.2 20-pin Header
	Power Supply	Redundant
	PSU Wattage	1200 W
	PSU Certification	80+ Titanium
	Chassis Dimensions	437 x 89 x 630mm

