

Supermicro SuperStorage Server SSG-2029P-E1CR24H 2U DP 24xSFF LSI 3108 2x10GbE RED PSU

Kod producenta: SSG-2029P-E1CR24H



Chassis Form Factor	Rack 2U
CPU Socket	LGA 3647 (Socket P)
# of CPU sockets	2
Supported CPU's	Intel Xeon Scalable 2nd Gen Intel Xeon Scalable 1stt Gen
Max CPU TDP	205 W
Chipset	Intel C624
Memory Type	DDR4 ECC LRDIMM DDR4 ECC RDIMM
Memory Speed	2666 MHz 2400 MHz 2133 MHz
# of DIMM's	16
Max Memory Size	2048 GB
Integrated GPU	Aspeed AST2500
# of 2.5 hot-swap bays	24
Backplanes	SAS3/SATA3
# of PCIe x16 3.0	3
# of PCIe x8 3.0	4
# of USB Ports	4 x USB 3.0 (rear) 1 x USB 3.0 Type A
# of SATA Ports	10
# of SAS Ports	8
Storage Controllers	8 x AHCI iSATA 6Gb/s 2 x sSATA 6Gb/s LSI 3108 12Gb/s AOC
Integrated RAID	0,1,5,10
Hardware RAID	0,1,5,6,10,50,60
# of Serial Ports	1 x Fast UART 16550 (header)
# of 10GbE Ports	2 x RJ45
Network Controllers	Intel x722 Port 10 Gigabit Base-T Intel x557 Port 10 Gigabit Base-T
Integrated BMC	IPMI Dedicated RJ45
BMC chip	Aspeed AST2500
TPM	1 x TPM 1.2 20-pin Header
Power Supply	Redundant
PSU Wattage	1200 W
PSU Certification	80+ Titanium
Chassis Dimensions	437 x 89 x 630mm
Uwagi	PCI-Express Slots Configuration: 3x PCI-E 3.0 x16 slots 4x PCI-E 3.0 x8 slots Slot 2 & 3 occupied by controller and JBOD Expansion Port Hot-swap Configuration: 24x Hot-swap 2.5" SAS3/SATA3 2x Optional 6Gb/s SAS3 M.2

Poniżej prezentujemy szczegółowy opis techniczny oferowanego produktu:

