

Supermicro SuperChassis SC846BE1C-R1K23B 4U 24xLFF RED PSU

Kod producenta: CSE-846BE1C-R1K23B



Chassis Form Factor	Rack 4U
# of 3.5 hot-swap bays	24
Power Supply	Redundant
PSU Wattage	1200W
PSU Certification	80+ Titanium
Chassis Dimensions	437 x 178 x 660mm

Poniżej prezentujemy szczegółowy opis techniczny oferowanego produktu:

Product SKUs

CSE-846BE1C-R1K23B • SuperChassis 846BE1C-R1K23B

Form Factor

• 4U chassis support for max. motherboard size - EE-ATX (13.68" x 13"), E-ATX (12" x 13"), ATX (12" x 10")

Processor Support

• Single and Dual Intel® and AMD processors

Dimensions

Height - 7" (178 mm)
Width - 17.2" (437 mm)
Depth - 26" (660 mm)
Gross Weight - 75 lbs (34.02 kg)
Packaging (W x H x L) - 34.3" (871 mm) x 26.5" (673 mm) x 13.5" (343 mm)
Available Color - Black

Expansion Slots

- 7 full-height & full-length expansion slot(s)

Drive Bays

- 24 x 3.5" hot-swap drive bay

Backplane

- 24-port 4U SAS3 12Gbps single-expander backplane, support up to 24x 3.5-inch SAS3/SATA3 HDD/SSD

Peripheral Drives

- Optional 2 x 2.5" hot-swap drive bay
- Optional 1 x 3.5" internal fixed drive bay
- Optional 2 x 2.5" internal fixed drive bay

Front Panel

Buttons - Power On/Off button
- System Reset Button
- 2 Network Activity LEDs
- Fan Fail/System Over Heat LED
LEDs - HDD activity LED
- Power Status LED
- Unit Identification (UID) LED

Motherboard (for CSE- 846BE1C-R1K23B)

X11SPH-nCTF H11DSI-NT
X11SPH-nCTPF X11DPH-T
X11DPH-I X11DPH-TQ
H11DSi H11SSL-NC
H11SSL-C H11SSL-i

Servers (for CSE- 846BE1C-R1K23B)

6049P-E1CR24L 6049P-E1CR24H

Systems Cooling

Fans - 3 x 8cm hot-swap redundant PWM cooling fan(s)
- 2 x 80mm rear hot-swap exhaust PWM fan(s)

System Monitoring

- Chassis intrusion switch

Operating Environment (System)

Operating Temperature Range - 5°C - 35°C (41°F - 95°F)
Non-Operating Temperature Range - -40°C - 70°C (-40°F - 158°F)
Operating Relative Humidity Range - 8% - 90% (non-condensing)
Non-Operating Relative Humidity Range - 5% - 95% (non-condensing)

Power Supply

1U 1200W/1000W Titanium Power Supply
W/PMbus W76xL360xH40mm
Power Efficiency - 96%
Total Output - 1000W with Input 100 - 127Vac
Power and Input - 1200W with Input 200 - 240Vac
- 1200W with Input 200 - 240Vdc
AC Input Frequency - 50-60Hz
Dimensions (L x W x H) - 336 x 76 x 40 mm
Output Type - Backplanes (gold finger)
- Max: 83A (100Vac - 127Vac)
+12V - Max: 100A (200Vac - 240Vac)
- Max: 100A (200 - 240)
+5Vsb - Max: 4A / Min: 0A
Power Distributor - PDB-PT846-2824
Certification - Titanium Certified

Regulatory (Power Supply)

- BSMI
Power Supply Safety / EMC - CCC
- CE/EMC
- FCC class A
- UL/CB

Strona firmowa produktu:

<https://www.superstorage.pl/supermicro-superchassis-sc846be1c-r1k23b-4u-24xlff-red-psu-p-3697.html>