

ASRock 1U2-X570/2T, Rack 1U, UP, AMD Ryzen, 2xLFF, 2x10GbE, Fixed PSU, IPMI

Kod producenta: 1U2-X570/2T



# of CPU sockets	1
Supported CPU's	AMD Ryzen 3000 AMD Ryzen 3000G AMD Ryzen PRO 3000 AMD Ryzen 4000 AMD Ryzen PRO 4000 AMD Ryzen 5000 AMD Ryzen PRO 5000
# of DIMM's	4
# of 3.5 fixed bays	2
# of 10GbE Ports	2 x RJ45
Integrated BMC	IPMI Dedicated RJ45
Power Supply	Fixed
PSU Wattage	265 W
Warranty	1 year standard 3 years on request

1U2-X570/2T

- Front I/O
- 1U Rackmount with 265W PSU
- supports AMD Ryzen 5000 Series Desktop Processors
- 4 DDR4 ECC/ non-ECC SO-DIMM, up to 32GB each
- Supports 2 fixed 3.5"drives and 2 fixed 2.5" 7mm drives
- On-board dual 10GbE RJ45
- Remote management (IPMI)

Specyfikacja

System	
Rozmiar/format	1U
Wymiary	250mm x 430mm x 43.5mm (9.84"D x 16.93"W x 1.71"H)
Obsługiwane płyty	X570D4I-2T
Front Panel	
Buttons	Power switch, System reset
LEDs	Power status, HDD, LAN activity LEDs
I/O Ports	1 DB15 (VGA) 2 Type-A (USB3.2 Gen1) 2 Type-A (USB3.2 Gen2) 2 RJ45 (10GbE) by Intel® X550-AT2 1 UID w/ LED
IPMI LAN	1 dedicated IPMI

Zewnętrzna zatoka / Storage	
Internal Side	Supports 2 fixed 3.5" drives and 2 fixed 2.5" 7mm drives 1 M-key (PCIe4.0* x4 or SATA 6Gb/s); Form factor: 2280 *Supports PCIe3.0 when using AMD Ryzen™ 4000 and 3000 G-Series Desktop Processors with Radeon™ Graphics
Zasilacz	
Rodzaj	Single PSU
Moc wyjściowa	265W
Efektywność	80-Plus Bronze
AC Input	100-240V, 50-60Hz
Chłodzenie	
Wentylator	3 Easy-swap 40x28 mm fans
Procesor	
CPU	Supports: AMD Ryzen™ 5000 and 3000 Series Desktop Processors AMD Ryzen™ 4000 and 3000 G-Series Desktop Processors with Radeon™ Graphics AMD Ryzen™ PRO 5000, 4000 and 3000 Series Desktop Processors
Socket	AM4 PGA 1331
Zasilanie	105W
Chipset	AMD X570
Pamięć operacyjna	
Pojemność	4 DDR4 SO-DIMM slots (2DPC)
Rodzaj	Supports DDR4 288-pin ECC*/non-ECC SO-DIMM *For AMD Ryzen Desktop Processors with Radeon Graphics, ECC support is only with Processors with PRO technologies.
DIMM Size Per DIMM	up to 32GB
DIMM Frequency	One DIMM: 1R DIMM @2933MT/s; 2R/2DR DIMM@2400T/s Two DIMMs: 2400MT/s
Napięcie	1.2V
Zarządzanie	
Kontroler BMC	ASPEED AST2500
IPMI Dedicated GLAN	1 x Realtek RTL8211E for dedicated management GLAN
Grafika	
Kontroler	ASPEED AST2500
VRAM	DDR4 16MB
BIOS	
Rodzaj BIOS	32MB AMI UEFI Legal BIOS
Cechy BIOS	Plug and Play (PnP) ACPI 2.0 Compliance Wake Up Events SMBIOS 2.8.0 Support ASRock Rack Instant Flash
Środowisko	
Temperatura	Operation temperature: 10°C ~ 35°C / Non operation temperature: -40°C ~ 70°C
Humidity	Non operation humidity: 20% ~ 90% (Non condensing)

Specyfikacja może ulec zmianie bez wcześniejszego powiadamiania. Marka i nazwy produktów są znakami towarowymi ich właścicieli. Działanie konfiguracji innych niż wynikające ze specyfikacji nie jest gwarantowane.

Strona firmowa produktu:

<https://www.superstorage.pl/asrock-1u2-x5702t-rack-1u-up-amd-ryzen-2x1ff-2x10gbe-fixed-psu-ipmi-p-5385.html>