

Supermicro SuperServer SYS-6029BT-HNC0R 2U DP 12xLFF IPMI RED PSU

Kod producenta: SYS-6029BT-HNC0R



Category	Compute Intensive Application HPC, Data Center, Enterprise
Order option	Complete System Only
Chassis Form Factor	RACK 2U
# of systems (nodes)	4
CPU Socket	LGA 3647 (Socket P)
# of CPU sockets (per node)	2
Supported CPU's	Intel Xeon Scalable 2nd Gen Intel Xeon Scalable 1st Gen
Max CPU TDP	205 W
Chipset	Intel C621
Memory Type	DDR4 ECC RDIMM DDR4 ECC LRDIMM
Memory Speed	2933 MHz 2666 MHz 2400 MHz 2133MHz
# of DIMM's (per node)	24
Max Memory Size	6 TB
Integrated GPU	ASPEED AST2500
# of 3.5 hot-swap bays (per node)	3
Backplanes	NVMeG3/SAS3/SATA3
# of PCIe x16 3.0 (per node)	2
I/O expansion modules (per node)	1 x SIOM PCIe 3.0 x16 (for Networking)
# of USB Ports (per node)	2 x USB 3.0
Storage Controllers	Broadcom 3008
# of M.2 2280 (per node)	2
Integrated BMC	IPMI Dedicated RJ45
BMC chip	ASPEED AST2500
TPM	1 x TPM 2.0 10-pin Header
Power Supply	Redundant
PSU Wattage	2200 W
PSU Certification	80+ Titanium
Rack Rails	Included
Chassis Dimensions	447 x 88 x 765 mm

Ze względu na wysoki stopień integracji platforma dostępna jest tylko i wyłącznie jako gotowy system wraz z CPU, RAM i HDD oraz dodatkowymi kartami rozszerzeń. Prosimy o kontakt z nami w celu przedstawienia oferty na interesującą Państwa konfigurację.

Strona firmowa produktu:

<https://www.superstorage.pl/supermicro-superserver-sys-6029bt-hnc0r-2u-dp-12xlff-ipmi-red-psu-p-6704.html>