

Supermicro A+ Server AS-2124BT-HNTR 2U DP 24xSFF 2x10GbE SIOM IPMI RED PSU

Kod producenta: AS -2124BT-HNTR



| | |
|-------------------------------------|--|
| Category | Compute Intensive Applications HPC, Data Center, Enterprise Server |
| Order option | Complete System Only |
| Chassis Form Factor | RACK 2U |
| # of systems (nodes) | 4 |
| CPU Socket | LGA 4094 (Socket SP3) |
| # of CPU sockets (per node) | 2 |
| Supported CPU's | AMD EPYC 7003 AMD EPYC 7002 |
| Max CPU TDP | 225 W |
| Chipset | System on Chip |
| Memory Type | DDR4 ECC RDIMM |
| Memory Speed | 3200 MHz |
| # of DIMM's (per node) | 16 |
| Max Memory Size | 4 TB |
| Integrated GPU | ASPEED AST2500 |
| # of 2.5 NVMe bays (per node) | 4 |
| Backplanes | NVMeG3/SAS3/SATA3 |
| # of PCIe x16 4.0 (per node) | 2 |
| I/O expansion modules (per node) | 1 x SIOM PCIe 4.0 x16 (for Networking) |
| # of USB Ports (per node) | 2 x USB 3.0 |
| # of M.2 22110 (per node) | 1 |
| # of Serial Ports (per node) | 1 x Fast UART 16550 (header) |
| Integrated BMC | IPMI Dedicated RJ45 |
| BMC chip | ASPEED AST2500 |
| TPM | 1 x TPM 2.0 20-pin Header |
| Power Supply | Redundant |
| PSU Wattage | 2200 W |
| PSU Certification | 80+ Titanium |
| Chassis Dimensions | 449 x 88 x 730 mm |

UWAGA !!!

Oferowany produkt to platforma służąca do budowy swojej własnej konfiguracji (nie zawiera CPU, RAM czy HDD). Jeżeli potrzebujesz kupić gotowy system wraz z CPU, RAM, HDD/SDD oraz innymi opcjami koniecznie wyślij do nas zapytanie. Posiadamy najlepsze ceny i dostępność na pełne konfiguracje. Zapewniamy pełne wsparcie techniczne do zakupionych u nas systemów.

Strona firmowa produktu:

<https://www.superstorage.pl/supermicro-server-as-2124bt-hntr-2u-dp-24xsff-2x10gbe-siom-ipmi-red-psu-p-7186.html>