

# Supermicro A+ Server AS-1015CS-TNR-EU 1U UP 4xLFF 2xAIOM IPMI RED PSU

Kod producenta: AS -1015CS-TNR-EU



|                        |                                                                     |
|------------------------|---------------------------------------------------------------------|
| Category               | Web Server, Firewall Application<br>Cloud Computing, Compact Server |
| Order option           | Complete System                                                     |
| Chassis Form Factor    | Rack 1U                                                             |
| CPU Socket             | LGA 6096 (Socket SP5)                                               |
| # of CPU sockets       | 1                                                                   |
| Supported CPU's        | AMD EPYC 9004                                                       |
| Max CPU TDP            | 360 W                                                               |
| Chipset                | System on Chip                                                      |
| Memory Type            | DDR5 ECC RDIMM                                                      |
| Memory Speed           | 4800 MT/s                                                           |
| # of DIMM's            | 12                                                                  |
| Max Memory Size        | 3 TB                                                                |
| Integrated GPU         | ASPEED AST2600                                                      |
| # of 3.5 hot-swap bays | 4                                                                   |
| # of PCIe x16 5.0      | 2                                                                   |
| I/O expansion modules  | 2 x AIOM PCIe 5.0 x16                                               |
| # of USB Ports         | 2 x USB 3.0                                                         |
| # of M.2 22110         | 2                                                                   |
| # of Serial Ports      | 1 x Fast UART 16550 (rear)                                          |
| Integrated BMC         | IPMI Dedicated RJ45                                                 |
| BMC chip               | ASPEED AST2600                                                      |
| TPM                    | 1 x TPM 2.0 10-pin Header                                           |
| Power Supply           | Redundant                                                           |
| PSU Wattage            | 860 W                                                               |
| PSU Certification      | 80+ Titanium                                                        |
| Rack Rails             | Included                                                            |
| Chassis Dimensions     | 43 x 437 x 650 mm                                                   |

**UWAGA !!!**

*Ze względu na wysoki stopień integracji platforma dostępna jest tylko i wyłącznie jako gotowy system wraz z CPU, RAM i HDD oraz dodatkowymi kartami rozszerzeń. Prosimy o kontakt z nami w celu przedstawienia oferty na interesującą Państwa konfigurację.*

