

Supermicro SuperServer SYS-6028U-TNRT+ 2U DP 12xLFF 4xNVMe 2x10GbE RED PSU

Kod producenta: SYS-6028U-TNRT+

Chassis Form Factor	Rack 2U
CPU Socket	LGA 2011 (Socket R3)
# of CPU sockets	2
Supported CPU's	Intel Xeon E5-2600v4 Intel Xeon E5-2600v3
Max CPU TDP	160W
Chipset	Intel C612 Wellsburg
Memory Type	DDR4 ECC 3DS LRDIMM DDR4 ECC LRDIMM DDR4 ECC RDIMM
Memory Speed	2400 MHz 2133 MHz 1866 MHz 1600 MHz
# of DIMM's	24
Max Memory Size	3072 GB
Integrated GPU	Aspeed AST2400
# of 3.5 hot-swap bays	12
# of 3.5 NVMe bays	4
Backplanes	SAS3/SATA3
# of PCIe x8 3.0	7
# of USB Ports	2 x USB 3.0 (rear) 2 x USB 3.0 (header) 1 x USB 3.0 Type A
# of SATA Ports	8
# of Super DOM	2
Storage Controllers	8 x AHCI iSATA 6Gb/s
Integrated RAID	0,1,5,10
# of Serial Ports	1 x Fast UART 16550 (header)
# of 10GbE Ports	2 x Base-T
Network Controllers	Intel x540 Dual Port 10 Gigabit Base-T
Integrated BMC	IPMI 2.0 KVM-over-LAN Virtual Media over LAN IPMI Dedicated RJ45 PHY
BMC chip	Aspeed AST2400
TPM	1 x TPM 1.2 20-pin Header
Power Supply	Redundant
PSU Wattage	1000W
PSU Certification	80+ Titanium
Rack Rails	included
Chassis Dimensions	437 x 89 x 647mm
Uwagi	HDD bays configuration: Optional 12x SAS3 ports via AOC Note: optional storage card is required to support more than 10 drives.

Poniżej prezentujemy szczegółowy opis techniczny oferowanego produktu:

Product SKUs		Chassis	
SYS-6028U-TNRT+ • SuperServer 6028U-TNRT+ (Black)		Form Factor Model • 2U Rackmount • CSE-829UAC-R1K02	
Motherboard Super X10DRU-i+		Dimensions and Weight	
Processor/Cache		Width Height Depth Weight Available Colors	
CPU Cores / Cache System Bus Note Note		• 17.2" (437mm) • 3.5" (89mm) • 28.46" (723mm) • Net Weight: 36 lbs (16.4 kg) • Gross Weight: 72 lbs (32.7 kg) • Black	
System Memory		Front Panel	
Memory Capacity Memory Type DIMM Sizes Memory Voltage Error Detection		Buttons LEDs	
On-Board Devices		Expansion Slots	
Chipset SATA IPMI Network Connectivity Graphics		PCI-Express Drive Bays Hot-swap	
Input / Output		Backplane	
SATA SAS NVMe LAN USB Video Serial Port / Header DOM		2U SAS/SATA backplane	
System BIOS		System Cooling	
BIOS Type BIOS Features		Fans	
Management		Power Supply	
Software Power Configurations		Total Output Power Dimension (W x H x L) Input +12V 12Vsb Output Type Certification	
		PC Health Monitoring	
		Voltage FAN Temperature LED Other Features	
		Operating Environment / Compliance	
		RoHS Environmental Spec.	

UWAGA !!!

Ze względu na wysoki stopień integracji platforma dostępna jest tylko i wyłącznie jako gotowy system wraz z CPU, RAM i HDD oraz dodatkowymi kartami rozszerzeń. Prosimy o kontakt z nami w celu przedstawienia oferty na interesującą Państwa konfigurację.

Strona firmowa produktu:
<https://www.superstorage.pl/supermicro-superserver-sys-6028u-tnrt-2u-dp-12x1ff-4xnvme-2x10gbe-red-p-su-p-989.html>